

## H.265+ 4chs POE NVR



### Features:

- Support 2chs 4K/4chs 5M Video access storage
- 1SATA (Max 8T each)
- POE Ethernet power supply; 4 standard POE ports
- H.265+/H.265/H.264
- Support VGA 1080P/HDMI 4K Output
- Support DHCP,FTP,DNS,DDNS,NTP,UPNP,EMAIL,3G, IP search, Alarm center and so on
- Support ONVIF Protocol; support GB28181 Protocol (Optional)
- Support WEB, CMS, VMS,MYEYE Platform, provide SDK for develop
- Support Mobile Phone Monitoring(IOS ,Android)
- Cloud Services,P2P,Alarm Information Push To Phone
- Support Multi-Language
- Support Multi-browser access(IE, Chrome, Firefox, Safari)

### Video

Model No.	WDM-TSNVR8804C3/POE	
Video compression	H.265+/H.265/H.264	
Video Input	2chs 4K/4chs 5MP	
Preview	4*D1/1*4K+3*D1 image display	
Playback	1*4K/2*4MP/4*1080P	
main processor	Hi3536	
Operation System	Embedded Linux	
Video management	video mode	Manual recording、timer recording、 motion detection recording、 alarm recording
	Video query	Time retrieval, calendar retrieval, event retrieval, channel retrieval
	Video Storage	Hard Disk Storage, network storage
	backups	network backup, USB, SATA

### Audio

Audio compression	G.711A
Voice intercom	Support

### Interface

Video Output	1*HDMI (Max 4K) /1*VGA (max 1080P)
Audio In/Out	42736
Alarm In/Out	--
Ethernet	1*100M(220M POE Transmit), RJ45 port
POE port	4 Standard POE Ports
USB	2*USB

### General

HDD	1 HDD
Capacity	max 8TB each
Power supply	DC48V2A
Consumption	<10W(Without HDD)
Working temperature	0℃--+55℃
Working humidity	10%--90%
Support	Seetong cloud/APP

### Accessories

Accessories	1pc power supply, Remote Controller, 1pc CD, 1pc user manual, 4pcs screws
-------------	---