

## CCTV 4chs 5.0MP Security Surveillance Alarm DVR Systems



- \* 1\*4chs HD Dvr,4chs video/network;
- \* 2\*outdoor 30m IR waterproof AHD cameras
- \* 2\*indoor 30m IR Dome cameras (metal/plastic case)
- \* 4\*18.3m(60 feet) Video+power cable
- \* 1\* 12v2A Power supply with 1 to 4 DC cable
- \* Not included HDD

Model Number	WDM-CAHD04M-B	WDM-CAHD04Q-B
--------------	---------------	---------------

### AHD Cameras specifications

#### Video

Sensor	XM350+SC5239	FH8538M+Sony IMX326
Resolution	5.0MP (2592*1944)	
Minimum Illumination	Low lux(0.0001lux)	
Day/Night Mode	Color During day/switches to B&W at night	
Signal System	PAL/NTSC	
Effective Pixel	PAL: (2592*1944)@25fps; PAL: (2592*1944)@30fps	
Video Standard	AHD/TVI/CVI/1200TVL CVBS Standard	

#### Lens and IR

Lens	3.6mm
IR Distance	Up to 30m
IR Cut Filter	yes

#### General

Waterproof	IP66
Indoor / Outdoor	Suitable for Indoor or Outdoor use
Power Input	DC12V1A (4pcs)
Working Temperature	-10°C ~+60°C

### DVR Specifications

Operating System	Embedded linux
------------------	----------------

#### Video&Audio

Video compression	H.264
Encode	4*5M@18fps(AHD)/4M (AHD)/ 3M (AHD)/1080P
Analog input	4*5M@18fps(AHD)/4M (AHD)/ 3M (AHD)/1080P
Hybrid input	2CH*5M(Analog)+2CH*5M(IP)
Audio Input	4 RCA Input

Audio Output	1 RCA Output
Audio compression	G.711A
<b>Recording</b>	
Compression Format	H.264
Recording Modes	Manual/Motion/Schedule
Hard drive	Internal SATA hard drive required for recording, support up to 4TB
<b>Network</b>	
LAN Connection	YES
Network Interface	RJ45
<b>Interface</b>	
Video input	4ch BNC
Video output	1ch VGA, 1ch HDMI
USB	2* USB 2.0
HDD	1*SATA port (Max 4TB/per)
<b>General</b>	
Power Supply	DC 12V
Back up method	External storage via USB
Temperature/Humidity	-20°C+50°C; -10%-90%
Remote Control	YES
<b>DVR Language</b>	
Russian, English, Finnish, French, German, Greek, Italian, Japanese, Poland, Portugal, Spanish, Thai, Turkey Romanian, Slovakia, Czech, Arabic, Swedish and so on	