

HD-AHD 700/1000TVL Super Mini Pinhole CCD Camera



Features

- 1, Using the high performance sensor, image is clear and delicate;
- 2, Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- 3, Analog HD 700TVL CCD video output;
- 4, Support the ultra low illumination;
- 5, Support automatic electronic shutter function, adapt to different monitoring environment;
- 6, DC12V
- 7, black; Φ 20mm

Accessories

- User Manual
- Warranty Card
- Screw fittings
- Desiccant

Specification

Product Name	HD-AHD 700TVL Super Mini Pinhole CCD Camera
Model No.	WDM-AHD6406G
Video	
Sensor	1/3" Sony CCD
Output resolution	700TVL
D/N Mode	IR cut Auto switching
Minimum Illumination	0.00LUX/F1.2(Led on)
Effective Pixel	PAL:976(H)*582(V)
	NTSC:976(H)*494(V)
Signal System	PAL/NTSC
Video Standard	AHD and CVBS Standard
Video Output	1CH AHD HD/CVBS Standard Singal Output(Switchable)
Max Transmission Distance	Common 75-3 cables can be up to 500m
Lens and IR	
Lens	3.6/6mm lens. CCD Lens
IR distance	not support
Function	
Shutter Speed	4/25s-1/45,000s
BLC	Off/Low/Medium/High/Highest
White Balance	Auto White Balance
HLC	Support
Operation Temperature	-10°C~55°C
Power Supply	DC12V
Dimension	black; Φ 20mm