

4CHS WIFI NVR System From Wardmay Professional CCTV Camera Suppliers



- * 4CH 720P/1080P WiFi NVR
- * Indoor/outdoor 20-30m WIFI 1.0/2.0 Megapixel IR waterproof IP cameras with adaptor, bracket.
- * Plug and Play, no need network paring
- * strong ability of singnal transmit up to crossing 1 to 4 walls, wifi distance:80-300 meters
- * **APP: XMEye**

IP Cameras specifications

Model	WDM-NKITR804HDE-XM	WDM-NKITR804HE-XM
Operating System	Embedded linux	
Image Sensor	XM510+H62 1/4" Progressive Scan Sensor	HI3516EV100+SC2235P 1/3" Progressive Scan Sensor
Resolution	720P	1080P
Frame Specification	H.264+ 1280*720@25fps	H.265+ 1920x1080@25fpS
S/N Ratio	>39.1dB	
Minimum Illumination	Color:0.1 Lux; B/W:0.01 Lux	
Lens	3.6MM	
Infrared distance	20-30m	
Waterproof	IP66	
White Balance	Auto	
Day&Night	IR cut filter with auto switch	
3D-DNR	Auto	
Privacy Masking	4 Zone Selectable	
Infrared lamp	3pcs X \varnothing 20 Lamp beads	
Power Input	DC12V1A (4pcs)	
Consumption	max 6W	
Interface	RJ45/WIFI 802.11b/g/n	
Operation temperature	-10°C to +50°C /30% to 80% RH	
Size & Weight	170mm*65mm; 0.35KG	

WIFI NVR Specifications

System

Operating System	Embedded linux OS	
Main processor	Hi 3520D	Hi 3536D
System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup	

Interface

Operator interface	16-bit true color graphic menu operation interface, support mouse operation
--------------------	---

Preview	1/4	
Video input (IP)	4*960P	4*1080P
Access bandwidth	24Mbps	
Forwarding bandwidth	25Mbps	
Video compression	H.264	H.265+
Display quality	Max 960P	Max 1080P
Playback quality	960P	1080P
Decode	4*960P	4*1080P
VR	Unsupport	
Motion detection	Support(depend on camera)	
Audio		
Audio compression	G.711A	
Intercom	Unsupport	
Record & playback		
Recording mode	Manual>Alarm>Dynamic Detection>Timing	
Local payback	4*960P	4*1080P
Search mode	Search by Time/Calendar/Event/Channel	
Record storage	HDD、Network	
Backup mode	Network backup, USB hard disk, USB burner, SATA burner	
External Interface		
Video output	1ch VGA, 1ch HDMI HD output	
Audio I/O	0/0	
Alarm I/O	0/0	
Network interface	1*RJ45 10M/100M Adaptive Ethernet port+4ch WIFI	
USB interface	2*USB2.0 ports	
HDD	1* SATA(Up to 8TB for each disk)	
ESATA	No	
Serial interface	No	
Other		
ONVIF	No	
Power supply	12V/2A	
Power Consumption	<10W(Without HDD)	
Work environment	Temperature:0℃-+55℃ , Humidity:10%—90%RH , Atm:86kpa—106kp	
Dimension	254mm*215mm*42mm	
Weight	1.05KG	
Package Informations		
Wifi NVR	1 set	
Wifi Camera	4 pieces	
Network line	1m*1	
Power adapter	DC12V2A(1 pcs); DC12V1A(4 pcs)	
USB Mouse	1 piece	
User Manual	1 piece	

Screw bag	4 pieces
Weight	3.5KG
Package Size	360mmx200mmx290mm