



- * Using the high performance sensor, image is clear and delicate;
- * Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- * AHD/TVI/CVI/1200TVL 4 in 1 video output;
- * can access to many brands HD DVR;
- * Support the ultra low illumination;
- * Support automatic electronic shutter function, adapt to different monitoring environment;
- * 50m night vision distance, 2pcs 4rd Generation (Lattice type) Array LED, DC12V
- * Metal, Waterproof IP66

Specification

Product Name	CCTV 2.0MP HD Video Security Surveillance IR Bullet AHD Camera				
Model No.	WDM-AHD6103G	WDM-AHD6103S	WDM-AHD6103U	WDM-AHD6103P	WDM-AHD6103K
Video					
Sensor	XM330+2235	FH8536+AR0232	V30E+Sony IMX323	NVP2441H+Sony IMX291	FH8550M+Sony IMX290
Output resolution	2.0MP (1920*1080)				
D/N Mode	IR cut Auto switching				
WDR	-	-	-	-	Support
DNR	2D DNR	2D DNR	2D DNR	3D DNR	3D DNR
Minimum Illumination	0.000LUX/F1.2(Led on)				
Effective Pixel	PAL: (1920*1080)@25fps				
	NTSC: (1920*1080)@30fps				
Signal System	PAL/NTSC				
Video Standard	AHD/TVI/CVI/CVBS standard				
Video Output	1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable)				
Max Transmission Distance	Common 75-3 cables can be up to 500m				
Lens and IR					
Lens	4/6/8mm fixed iris lens				
IR distance	50m night vision distance, 2pcs 4rd Generation (Lattice type) Array LED				
Function					
Shutter Speed	4/25s-1/45,000s				
BLC	Off/Low/Medium/High/Highest				
White Balance	Auto White Balance				
HLC	Support				
Operation Temperature	-10°C~55°C				
Power Supply	DC12V				