

## IHD CCTFV Total Solution

## www.wardmay.com



- \* Using the high performance sensor, image is clear and delicate;
- \* Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- \* AHD/TVI/CVI/1200TVL4 in 1 video output;
- \* can access to many brands HD DVR;
- \* Support the ultra low illumination;
- \* Support automatic electronic shutter function, adapt to different monitoring environment;
- \* 30m night vision distance, 30pcs F5 ir led, DC12V
- \* 4" steel vandalproof dome. Waterproof:IP65

Specification	
Product Name	CCTV 3.0MP IR Dome HD Video Security Surveillance AHD Camera
Model No.	WDM-AHD6136V
Video	
Sensor	V30E+AR0330
Output resolution	3.0MP(2048x1536)
D/N Mode	IR cut Auto switching
Minimum Illumination	0.000LUX/F1.2(Led on)
Effective Pixel	PAL: (2048x1536)@25fps
	NTSC: (2048x1536)@30fps
Signal System	PAL/NTSC
Video Standard	AHD/TVI/CVBS standard
Video Output	1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable)
Max Transmission Distance	Common 75-3 cables can be up to 500m
Lens and IR	
Lens	2.8-12mm manual iris lens
IR distance	30m night vision distance, 30pcs F5 ir led
Function	
Shutter Speed	4/25s-1/45,000s
BLC	Off/Low/Medium/High/Highest
White Balance	Auto White Balance
HLC	Support
Operation Temperature	-10°C~55°C
Power Supply	DC12V