


Combinable HD-Cvi/Tvi/Ahd Passive CCTV UTP BNC Video Balun																													
	Specifications																												
	<table border="1"> <tr> <td>Model</td> <td>WDM-UTP6000HD-C</td> </tr> <tr> <td colspan="2">Transmission distance</td> </tr> <tr> <td>CVBS</td> <td>1200TVL / 600M</td> </tr> </table>	Model	WDM-UTP6000HD-C	Transmission distance		CVBS	1200TVL / 600M																						
Model	WDM-UTP6000HD-C																												
Transmission distance																													
CVBS	1200TVL / 600M																												
WDM-UTP6000HD-C	<table border="1"> <tr> <td>HD-AHD</td> <td>720P/600M, 1080P/450M.</td> </tr> <tr> <td>HD-TVI</td> <td>720P/500M, 1080P/380M</td> </tr> <tr> <td>HD-CVI</td> <td>720P/600M, 1080P/450M.</td> </tr> </table>	HD-AHD	720P/600M, 1080P/450M.	HD-TVI	720P/500M, 1080P/380M	HD-CVI	720P/600M, 1080P/450M.																						
HD-AHD	720P/600M, 1080P/450M.																												
HD-TVI	720P/500M, 1080P/380M																												
HD-CVI	720P/600M, 1080P/450M.																												
Features	<table border="1"> <tr> <td colspan="2">Technical specifications</td> </tr> <tr> <td>Wire Type</td> <td>UTP5</td> </tr> <tr> <td>UTP Connection</td> <td>"Press-Fit" terminal blocks</td> </tr> <tr> <td>Video Format</td> <td>HD-CVI/TVI/AHD, NTSC, PAL, and SECAM</td> </tr> <tr> <td>Case</td> <td>ABS Plastic</td> </tr> <tr> <td>Frequency Response</td> <td>DC to 60MHz</td> </tr> <tr> <td>Attenuation</td> <td>0.5dB typ</td> </tr> <tr> <td>CMRR</td> <td>60 dB</td> </tr> <tr> <td>Surge protection</td> <td>4KV</td> </tr> <tr> <td>ESD</td> <td>8KV</td> </tr> <tr> <td>Power</td> <td>No power required</td> </tr> <tr> <td>Working Temperature</td> <td>-10°C to +50°C</td> </tr> <tr> <td>Storage Temperature</td> <td>-30°C to +70°C</td> </tr> <tr> <td>Humidity</td> <td>0 to 95%</td> </tr> </table>	Technical specifications		Wire Type	UTP5	UTP Connection	"Press-Fit" terminal blocks	Video Format	HD-CVI/TVI/AHD, NTSC, PAL, and SECAM	Case	ABS Plastic	Frequency Response	DC to 60MHz	Attenuation	0.5dB typ	CMRR	60 dB	Surge protection	4KV	ESD	8KV	Power	No power required	Working Temperature	-10°C to +50°C	Storage Temperature	-30°C to +70°C	Humidity	0 to 95%
Technical specifications																													
Wire Type	UTP5																												
UTP Connection	"Press-Fit" terminal blocks																												
Video Format	HD-CVI/TVI/AHD, NTSC, PAL, and SECAM																												
Case	ABS Plastic																												
Frequency Response	DC to 60MHz																												
Attenuation	0.5dB typ																												
CMRR	60 dB																												
Surge protection	4KV																												
ESD	8KV																												
Power	No power required																												
Working Temperature	-10°C to +50°C																												
Storage Temperature	-30°C to +70°C																												
Humidity	0 to 95%																												
<ul style="list-style-type: none"> * Compatible with all HD-CVI, HD-TVI, HD-AHD Cameras and analog Cameras * No power required * 60dB cross talk and noise immunity * Compact size and easy installation * Built-in transient suppression protection * 1000V anti surgeprotection, strong anti-interference and noise reduction function * Joining by screws video transfer 																													