

H.265 2.0MP Starlight Network Day and Night Security IP Camera



Features

*Super Starlight Chips (SONY 307)

*Super clear day and night color image

*Support ONVIF 2.4 protocol, H.265 profile

*Intelligent 2D、3D DNR

*Intelligent dimming (according to the intensity of the ambient light to change the brightness of the fill light, prevent overexposure, faster recognition of person faces)

*Low illumination, no need to add too much light, two lights like two similar indicators, not dazzling, good quality.

*Support onvif

*With waterproof microphone & bracket

* Support two way audio, with horn interface

Dimension



Accessories

User manual

CD

Guarantee card

Screw

Model	WDM-H265IP8200SL
	H.265 2.0MP Starlight Network Day and Night Security IP Camera
Image Sensor	1/2.8" 2.0M Pixel Sony IMX307 CMOS
Dynamic Range	100dB
SNR	≥50dB (AGC OFF)
Lens	4/6mm lens
Illumination	0.0001Lux@F1.2(Color Mode); 0.0001 Lux@F1.2(B&W mode); 0Lux(IR CUT ON)
D/N mode	Auto IR-CUT switch, B/W, Color, Outer control
Gain Control	Auto/ Manual
White Balance	Auto, Indoor, Outdoor, Sodium Lamp, Manual
DNR	Support 2DNR, 3DNR
Exposure Mode	Program mode (customizable shutter interval), shutter mode (1/5-1/20,000s), support slow shutter
Video Compression	H.265 Main Profile / H.264 High profile / M-JPEG
Max Resolution	1920x1080@25fps
Video Resolution	Main stream: 1920x1080、1280x960、1280x720、720x576、640x480
	Substream: 640x480、480x360、352x288、320x240、176x144、OFF
	MJPEG: 1280x720、OFF
Output code rate	CBR or VBR: 32K~10M
OSD	Support Channel name, date on screen
Visit NO.	3 Users in Mainstream, 6 Users in Substream
Network Protocols	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS、P2P
ONVIF Protocol	Standard ONVIF2.4
Compatibility	Support HIKVISION、DAHUA、XM CMS、SEETONG UC2、Aebell NVR I8 ONVIF platform、NVR ONVIF protocol
Mobile P2P	Support Android、IOS visit
Network interface	1ch 10/100BaseT Ethernet, RJ45
Power	12V2A/POE
Working Temp	-30°C ~60°C
Working humidity	0%-90% RH (NO CONDENSING)