

H.265 4X Zoom 1080P WiFi Speed Dome IP Camera



Features

- * 4" double layer metal body construction, IP66 rate protection
- * HD Imager Sensor, 4X optical zoom
- * HD-IP digital interface output, 2.0MP high definition image
- * PWM function, intelligent IR illumination & power consumption is variable, dependant the zoom factor
- * IR distance 60M
- * ONVIF2.4 compatible; good compatibility with NVRs like DAHUA, HIKVISION , JUFENG and AXXON , Milestone and so on

* APP: Eseecloud

Dimension



Accessories

- Instruction book
- Warrant card
- Screw fittings
- Desiccant

Model Number	WDM-IP8854C-Wifi
Camera	
Image Sensor	HI3516E+ SC2232
Effective Pixels	2.0MP(1920x1080)
Resolution Ratio	1920*1080@20fps
Auto Control IR LED	PWM
Lens	f=2.8mm-12mm(4X Zoom)
Leds	6 pcs IR led
IR distance	Up to 60 meters
Dome	
Rotation Range	Pan: 0°~360°, Tilt: 0°~93°
Pan rotation speed	45°/s
Tilt rotation speed	30°/s
Auto Flip	Horizontal 180°, Vertical 93°
A-B scan	User programmabel(scan speed 1-9 levels setting available)
Preset points	220
Inspection teams	3 groups(Max.16 points, dwell time user electable)
Mechanical zero calibration	Support
WiFi and Network	
WiFi Protocol	802.11b/g/n
Wireless distance	≥ 150M
WiFi Safe mode	WEP\WPA\WPA2
WiFi antenna	Enhanced 5db antenna
Mobile View	Support Android/IOS Smart Phone
APP	Eseecloud
TF card storage	Supports 128G
Software Control	Software Control
Software Control	PELCO instruction set
Video and Audio	
Video Compression	H.265/H.264/M-JPEG
Voice intercom	Built-in microphone and speaker
Audio Compression	AAC
General	
waterproof	IP66
Power	DC12V3A
Operating temperature	-40℃~+60℃
Consumption	≤ 15W
Lightning Protection	Transient voltage 6000V