



Packaging Ink Jet Printer

HAE-2000

TIJ printer can print date, character, counters, image, barcode, variable data

packaging inkjet printer is mainly used in packaging printing, date printing, employee serial numbers printing, products label printing.

FDA CE SGS www.chinahae.com

Hardware technical parameters:

Printhead technology	HP TIJ 2.5
one Printhead height	0.5inch(12.7mm)
Size	114mmx88mmx103mm(not include the screen)
Interface	USB/RS232
Printing resolution and the printing speed which it can support at most	600x600dpi (30m/min) 600x300dpi (60m/min) 600x150dpi (120m/min) 300x600dpi (30m/min) 300x300dpi (60m/min) 300x150dpi (120m/min) 300x600dpi (high speed model)(60m/min) 300x300dpi (high speed model) (120m/min) 300x150dpi (high speed model) (304m/min)
Ink supply system	configure the external large capacity ink supply system
Sensor	support several external sensor (NPN, contact type)
Synchronizer	support fixed speed inputed and 300PPI synchronizer(standard)
Power requirement	110-240V/AC 50/60Hz Power :90W
Working environment	temperature 5°C-35°C, humidity 10%-90%
Storage environment	temperature -15°C-85°C, humidity 5%-95%, non-condensing environment(the ink cartridge except)

Software technical parameter

(Edit contents such as character, barcode, image and so on. Use U-DISK for data storage dispense with PC when printing)

Model software using system	XP operating system (Professional edition), other should be specifically stated
Static object	static next, image, static barcode
Dynamic object	Counter, texts, numbers, time,date,
Dynamic text	support dynamic text which can be 127 characters at most
Dynamic time	at most 10 every single page
Dynamic date	at most 10 every single page
Counters	at most 10 every single page
The length of single page	MAX: 1.2m MIN:5mm