



Features:

1. Pressure Rating: 1000PSI/PN63
2. Working Temperature: -10° C-150° C
3. Reduce Port
4. Investment Casting
5. Blow-out Proof Stem
6. Sanitary Design
7. PED97/23 EC
8. Thread: ASME B1. 20.1 BS21, DIN2999/259, ISO228-1, ISO7/1, JIS B 0203
9. Inspection Testing: API598, EN12516-2

1"	15	65	34.5	23
3/4"	12.5	54	31	23
1/2"	9.2	46	27.5	23
3/8"	7	43	25	23
1/4"	7	43	25	23
1/8"	6.5	40.5	25	23
SIZE	d	L	H	W

9	CAP	CF8/CF8M	1	
8	BALL SEAT (B)	PTFE	1	
7	BALL	304/316	1	
6	BODY	CF8/CF8M	1	
5	BALL SEAT (A)	PTFE	1	
4	"O"RING	NBR	2	
3	STEM	304/316	1	
2	BOLT	304	1	
1	LEVER	ALUMINUM ALLOY	1	
NO.	NAME	MATERIAL	Q' TY	
制图	审核	材质	比例	备注
产品名称		Mini Ball Valve F/M (CW MINI-FM)		
CangZhou Co-Win Metal Products Co., Ltd				