


DWH 650° C Glass Fiber Braided Fireproofing Sleeve

Product introduction:

DWH high temperature sleeve is made of alkali-free glass fiber filament braided sleeve which are dried with steep special flexible resin after high temperature treatments.

With its high temperature resistance performance, it's widely used in electrical machine, electric appliance, automobile and other high temperature application industry.

Product Feature:

Thermal Class	C
Size/inner diameter:	4mm-50mm
Color:	 black, red & blue, accept customized
Working temperature:	-70°C -650°C
Breakdown voltage:	1kv

Product Dimension:

PART NO.	INNER DIA./mm		WALL THICK /mm	
	Nominal	Tolerance	Min.	Max.
DWH-040	4	±0.30	0.2	0.6
DWH-050	5	±0.30	0.2	0.6
DWH-060	6	±0.30	0.2	0.6
DWH-070	7	±0.30	0.2	0.6
DWH-080	8	±0.30	0.2	0.6
DWH-090	9	±0.50	0.3	0.8

DWH-100	10	±0.50	0.3	0.8
DWH-120	12	±0.10	0.3	0.8
DWH-140	14	±1.0	0.3	0.8
DWH-160	16	±1.0	0.4	1.0
DWH-180	18	±1.0	0.4	1.0
DWH-200	20	±1.0	0.4	1.0
DWH-220	22	±2.0	0.5	1.5
DWH-250	25	±2.0	0.5	1.5
DWH-300	30	±2.0	0.5	1.5
DWH-350	35	±2.5	0.6	1.5
DWH-400	40	±2.5	0.6	1.5
DWH-450	45	±2.5	0.7	1.5
DWH-500	50	±2.5	0.7	1.5

