

玻璃纤维液体滤材-ZS 系列

Glass Microfiber Liquid Filter Media-ZS Series

500Kg	500Kg	500Kg	-----	1000Kg
-------	-------	-------	-------	--------

型号 项目	ZSU1	ZSH3	ZSH5	ZS10	ZS15	ZS20	ZS25	ZS30
过滤精度 um	1	2-3	4-6	8-12	13-17	18-22	23-27	28-32
定量 (±10g/m <sup>2</sup> ) basis weight								
<b>Basis weight</b>								
双面复合 Both-composit	130	130	130	130	130	130	130	130
单面复合 EachSide-com posit	100	100	100	100	100	100	90	90
透气度 air permeabilit								
l/m <sup>2</sup> .sec	20	50	90	160	200	250	300	420
阻力 resistance								
mm H <sub>2</sub> O	41	15	9	5	4	3	2	1
Pa	400	150	85	50	40	30	20	15
平均孔径 mean pore size								
um		20	30	40	60	90	120	150
过滤效率 efficiency (0.3U@5.3cm/s)								
%	99.99	95	80	60	45	35	25	15
抗张强度 Tensile strength								
KN/m	2	2	2	2	2	2	2	2
厚度 Thickness								
mm	0.5±0.1mm(双面), 0.4±0.1mm(单面)							