

4-Axis U-type Glue Dispensing Machine

3. Four-Axis U-type Glue Dispensing Machine&Robot



FEATURES

Style: X-2-DY-Z / X- 2-DY-2Z / X-2-DY-4Z

The device can replace the manual dispensing operation specific, mechanized production; the operation is simple and convenient, fast and accurate operation; program files through U disk upload / download, convenient data management and preservation; the machine with the needle control buttons, no need of external teaching device, is more convenient than the similar products Chinese / debugging; English operation interface.



Model		JT-D4210	JT-D5410
Working range(mm)	X-axis	200mm	400mm
	Y1/Y2/Y3/Y4-axis	200mm	400mm
	Z-axis	80mm	120mm
Adhesive&Glue Heating Temperature Range		0-360°C	
Max Load(kg)	Y-axis	10kg	
	Z-axis	5kg	
Moving Speed(mm/sec)		X Y Z-Axis 0.1-800mm/second	
Resolution(mm/Axis)		0.01mm/axis	
Repetitive Positioning Accuracy		+/-0.01mm/axis	
Programme Display		Hand-held box or LCD Box (optional computer)	
Motor System		Servo Micro-step Motor	
Interpolation Function		3 axis(3D stereoscopic space for any route)	
Driving Method		Conveyor&Synchronous driving belt	
Direction&Axis		Three Axis: X Y Z	
Programme Way		Hand knob or computer(optional)	
I/O Signal Port		8Intuts/8 Outputs(optional computer program/PC)	
External Interface		USB	
Power		AC220V 50/60HZ(OPTIONAL)	
Working Condition	Temperature	10-40°C	
	Humidity	20-90% no condensation	
Dimension(mm)		430*360*550mm	700*600*850mm
Weight(kg)		45KG	75kg