

Chamber filter press Features:

- 1.Short working cycle and high efficiency.
- 2.Big capacity. Unique plate design makes filtrate discharge more smoothly to make higher processing capacity.
- 3.Good filtering performance. Our filter press can endure higher feeding pressure, so that get lowest cake moisture.
- 4.Low running cost. According to CE standard, our filter press has remarkable performance to decrease the running cost.
- 5.Filter plate are made of reinforced polypropylene with features of high strength, corrosion resistance, nontoxic and odorless.
- 6.According to your material we will recommend special filter cloth, which can improving the filtering accuracy and efficiency .
- 7.Main beam material is Q235B/Q345B, with sand blasting processing.
- 8.Hydraulic station adopt ABB motor ensure stable performance.
- 9.Hydraulic squeezing ensures no leakage to avoid secondary pollution.
- 10.Cabinet elements adopts international famous brands: Siemens Schneider etc.

Specification	Filter area (m ²)	Filter plate size (mm)	Filter cake thickness (mm)	Filter chamber volume (L)	Filter plate number (pcs)	Filtrating pressure (Mpa)	Motor power (kw)	Weight (kg)
XYZ30/870-30U	30	870*870	30	427	23	0.6	2.2	3046
XYZ40/870-30U	40			534	29			3593
XYZ50/870-30U	50			748	38			4057
XYZ60/870-30U	60			902	46			4597
XYZ70/870-30U	70			1056	54			5136

XYZ80/870-30U	80	1000* 1000		1210	62	0.6	4.0	5636
XYZ50/1000-30U	50			752	28			4128
XYZ60/1000-30U	60			908	34			4636
XYZ70/1000-30U	70			1063	40			5143
XYZ80/1000-30U	80			1219	46			5651
XYZ100/1000-30U	100			1505	57			6628
XYZ120/1000-30U	120			1816	69			764



Abby Song

 +86-18701854523	 +86-18701854523
 abbasong249	 +86-18701854523
 +86-18701854523	 sales1@filterpressure.com