

B:2 prongs for solid wire(SS)

1. Electrical Test:

- A:250V AC max at 2 Amps
- B:Dielectric with standing 500volts AC
- C:Insulation Resistance:500 mega Ω
- D:Termination Resistance:35 mega Ω

2. Mechanical:

- A:Cable to Plug tensile strength 20LBs (89N) min
- B:Durability:1000 mating cycles

Ordering Code:

ATRP6P2C - X - B - X - 002  
 ①            ②            ③            ④            ⑤

1. Series:

2. Housing Material:

- A:UL 94V-0
- B:UL 94V-2

3. Contact Type:

- B:2 prongs for solid wire(SS)


4. Gold plating :

- A:1u" B:3u"
- C:6u" D:15u"
- E:30u" F:50u"

5. Serial number:

Unless Otherwise specified tolerance  
 X. ±0.35 X.XX: ±0.20  
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm  
 DRAW Wu Feng Rong DATE 16/09/2019  
 CHECK BobYang DATE 16/09/2019



ANTENK ELECTRONICS CO., LTD  
 Http://www.antenk.com  
 E-mail:sales@antenk.com

TITLE: Plug 6P2C Serial unshielded Type

DRAWING NO: ATRP6P2C-XBX-002

PRODUCT NO: ATRP6P2C-XBX-002

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		