

FPC0.3 - ① - ② - ③ - ④ - ⑤ - ⑥ - ⑦


Specifications:
 Material And Finish:
 Insulator:Nylon66 UL94V-0
 Contact:Phosphor Bronze, Tin plated
 Rating:
 Current Rating:0.3 Amp
 Voltage Rating:30V AC/DC
 Operating Temperature Range:-25° ~+85° C

- ① 0.3mm FPC Series
- ② Contact NO:
XX=XXpin
For example:
10=10pin
- ③ APPEARANCE
RM:SMT Right Angle
RT:DIP Right Angle
SM:SMT Straight
ST:DIP Straight
- ④ Contact type
D: Dual contact
- ⑤ Packing Type
T: Tube packing
A: tray packing
R: tape & reel
- ⑥ Plating:
G0:Gold flash
G1: 3U"gold
SN: MATT-TIN 90-120U"
S0: SELECTIVE GOLD
S1: SELECTIVE GOLD 3U"
- ⑦ Series number
1

PIN NO. (N)	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F	NOTES
09	4.90	1.80	2.40	3.03	4.35	3.00	
11	5.50	2.40	3.00	3.63	4.95	3.60	
13	6.10	3.00	3.60	4.23	5.55	4.20	
15	6.70	3.60	4.20	4.83	6.15	4.80	
17	7.30	4.20	4.80	5.43	6.75	5.40	
19	7.90	4.80	5.40	6.03	7.35	6.00	
21	8.50	5.40	6.00	6.63	7.95	6.60	
23	9.10	6.00	6.60	7.23	8.55	7.20	
25	9.70	6.60	7.20	7.83	9.15	7.80	
27	10.30	7.20	7.80	8.43	9.75	8.40	
29	10.90	7.80	8.40	9.03	10.35	9.00	
31	11.50	8.40	9.00	9.63	10.95	9.60	
33	12.10	9.00	9.60	10.23	11.55	10.20	
35	12.70	9.60	10.20	10.83	12.15	10.80	
37	13.30	10.20	10.80	11.43	12.75	11.40	
39	13.90	10.80	11.40	12.03	13.35	12.00	
41	14.50	11.40	12.00	12.63	13.95	12.60	
43	15.10	12.00	12.60	13.23	14.55	13.20	
45	15.70	12.60	13.20	13.83	15.15	13.80	
47	16.30	13.20	13.80	14.43	15.75	14.40	
49	16.90	13.80	14.40	15.03	16.35	15.00	
51	17.50	14.40	15.00	15.63	16.95	15.60	
53	18.10	15.00	15.60	16.23	17.55	16.20	
55	18.70	15.60	16.20	16.83	18.15	16.80	Long Cover type
57	19.30	16.20	16.80	17.43	18.75	17.40	
59	19.90	16.80	17.40	18.03	19.35	18.00	
61	20.50	17.40	18.00	18.63	19.95	18.60	
63	21.10	18.00	18.60	19.23	20.55	19.20	
65	21.70	18.60	19.20	19.83	21.15	19.80	
67	22.30	19.20	19.80	20.43	21.75	20.40	
69	22.90	19.80	20.40	21.03	22.35	21.00	
71	23.50	20.40	21.00	21.63	22.95	21.60	

Unless Otherwise specified tolerance
 X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
 DRAW Jack Bao DATE 10/28/2018
 CHECK BobYang DATE 10/28/2018



Antenk ANTENK ELECTRONICS CO., LTD
 Http://www.antenk.com
 E-mail:sales@antenk.com

TITLE: 0.3mm Pitch 1.0H SMT Right-Angle
 Dual Contact Back-Lock Type
 DRAWING NO:FPC0.3-XXRMDXX1
 PRODUCT NO:FPC0.3-XXRMDXX1

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		