

HSF



ROHS





SPECIFICATION

Current Rating: 1.5 Amp
 Insulation Resistance: 1000M ohms min
 Contact Resistance: 20M ohms max
 Dielectric Withstanding: AC500V
 Operating Temperature: -65°C to +125°C
 Contact Material: Brass
 Insulator Material: PA6T,UL 94V-0 Black

Ordering Code:

PHDS04 - X - X - D - A-B - X - X - X
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series No:
- ② No. of Contacts: 02 To 80
- ③ Contact Plating:
 G0: Gold flash S0: Selective
 G1: 3u" Gold S1: Selective 3u"
 G2: 5u" Gold S2: Selective 5u"
 G3: 10u" Gold S3: Selective 10u"
 G4: 15u" Gold S4: Selective 15u"
 G5: 30u" Gold S5: Selective 30u"
 SN: Tin
- ④ Connector Type: D: Dual
- ⑤ Pin Length:
 A: 0400=4.00mm
 B: 0280=2.80mm
 Please mark the desired length in the A/B
- ⑥ Insulator Material:
 A: PBT
 B: PA6T
 C: LCP
 D: PA46
 E: PA9T
- ⑦ Packing:
 A: Tray
 B: Bag
 T: Tube
 U: Tube+CAP
 R: Tape&Reel
 W: Tape&Reel+CAP
- ⑧ Plastic High:
 H1: 1.5mm
 H2: 2.0mm



PCB LAYOUT

Standard IE P/N : PHDS04-10-G0-D-0400-0280-B-B-H1

A	B	Unless otherwise specified tolerance	
4.00	2.80	X. XX: ±0.20	X. XXX: ±0.15
Optional		SCALE: As Shown	UNIT: mm

Antenk ANTENK ELECTRONICS CO., LTD
 Http://www.antenk.com
 E-mail:sales@antenk.com

DRAW	DATE
YG ZHONG	01/05/2016
CHECK	DATE
BobYang	01/05/2016

TITLE: 2.00mm Pin Header Dual Row Straight Type

2016/10/25	
DATE	

DRAWING NO: PHDS04-XXD-0400-0280-XXX
 PRODUCT NO: PHDS04-XXD-0400-0280-XXX

REV	DESCRIPTION	DATE
	Increase packing method and material	2016/10/25