

PCB LAYOUT

Dimension I & Ordering Information

	NO. of Positions	A	B	Type
A1	20	25.40	22.86	Without Bar
A2	24	30.48	27.94	
A3	28	35.56	33.02	
A4	32	40.64	38.10	
A5	40	50.80	48.26	
A6	20	25.40	22.86	With Bar
A7	24	30.48	27.94	
A8	28	35.56	33.02	
A9	32	40.64	38.10	
A10	40	50.80	48.26	
A11	42	53.34	50.80	
A12	48	60.96	58.42	
A13	64	81.28	78.74	

TECHNICAL DATA

Material:
 Pin: brass, machined CuZn38pb2
 Plating:
 Tin plated : 2um/80u"Ni, 5um/200u"Sn
 Gold plated: 2um/80u: nickelfull gold
 Insulator black(housing): PPS(UL94V-0)
 Electrical:
 Current rating: 3Amps/contact max
 Contact resistance: ≤ 4mΩ/contact
 Insulation resistance: ≥ 1000MΩ at V=100V
 Operating voltage : 60VAC/DC
MECHANICAL:

Operating temperatures: gold plated : -55°C ~ +105°C
 Tin plated: -40°C ~ +105°C
 Soldering temperature: +260°C , 10s max


Ordering Code:

MIMEM02A - X - X - X
 ① ② ③ ④

- ① Series No:
- ② Type selection
 A1 A2 A3
 A4...
- ③ Pin Plating
 S1: Tin 150"
 S2: Tin 200"
 G0: Gold flash
 G1: 3u" Gold
 G2: 5u" Gold
 G3: 10u" Gold
 G4: 15u" Gold
 G5: 30u" Gold
- ④ Packing
 A: Tray
 B: Bag
 C: Tube
 D: Tape & Reel

Unless Otherwise specified tolerance
 X: ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
 DRAW Mo Guo Xuan DATE 16/10/2018
 CHECK Bob Yang DATE 16/10/2018



Antenk ANTENK ELECTRONICS CO.,LTD
 Http://www.antenk.com
 E-mail: sales@antenk.com

TITLE: 2.54mm Pitch IC Sockets adapter SMT spacing 15.24mm

DRAWING NO: MIMEM02A-XXX

PRODUCT NO: MIMEM02A-XXX

2	Change of order number	18-10-15
REV	DESCRIPTION	DATE