

	NO	P3.91	P4.81
Module	Pixel Pitch(mm)	3.91mm	4.81mm
	Module Size(mm)	250*250mm	250*250mm
	Module Resolution(pixel)	64*64	52*52
	LED Type	SMD2121	SMD2727
	Scan Mode	1/16scan	1/13scan
	Application scene	Indoor	Indoor
Cabinet	Cabinet Size(mm)	500×500mm/500×1000mm	500×500mm/500×1000mm
	Cabinet Resolution(pixel)	128*128/128*256	104*104/104*208
	Material	AL	AL
	Cabinet Weight(KG)	8kg/13kg	8kg/13kg
	Pixel Density	65536	62500
Display	Brightness	1000cd/ m ²	1100cd/ m ²
	Refresh Rate(HZ)	≥3840	≥3840
	Gray level	16bit	16bit
	Avg.Power Consumption	190W/ m ²	800W/ m ²
	Max.Power Consumption	480W/ m ²	400W/ m ²
	Viewing Angle	H:140° , V:140°	H:140° , V:140°
	Service Access	Full front access	Full front access
	Operating Temp/Humidity	- 30°C ~ 60°C	- 30°C ~ 60°C
	Storage Temp/Humidity	10% ~ 90%RH	10% ~ 90%RH
	IP Grade	IP65	IP65
Best viewing distance	4-30m	5-30m	