

Silicone adjuvant QS-326

1. Description

QS-326 spray adjuvant is a super-spreading surfactant based on a trisiloxane ethoxylate. QS-326 spray adjuvant lowers the surface tension of spray solutions, beyond that which is achievable with conventional adjuvants.

Typically, QS-326 spray adjuvant (@ 0.1 wt %) gives an aqueous surface tension of <22 mN/m. On the other hand, an octylphenol ethoxylate containing 10 EO units (a commonly used nonionic surfactant) at 1.0 wt % gives a surface tension of only 30 mN/m.

QS-326 spray adjuvant helps lower the aqueous surface tension more effectively than conventional spray adjuvants. Because QS-326 spray adjuvant is a super-spreading surfactant, the contact angle of spray solutions on leaf surfaces is reduced, leading to an increase in spray coverage .

Additionally, under specific conditions, QS-326 spray adjuvant promotes rapid uptake of agrochemicals into plants via stomatal infiltration. Spray solutions taken into plants in this way become rainfast, thereby improving application reliability.

QS-326 spray adjuvant is nonionic in nature, making it useful with a broad range of agrochemical formulations.

2. Key Features And Typical Benefits

- Superspreader
- Promotes spray volume reduction
- Promotes rapid uptake of agrochemicals (rainfastness)
- Improves spray coverage
- Nonionic
- Meets requirements of EPA 40CFR§180.910



3. Typical Physical Properties

Property	Result
Surface Tension (0.1%, mN/m) ^(a)	21.5
Cloud Point (1 wt%), °C	<10
Viscosity (cst @ 25°C)	7
CMC (Wt%) ^(b)	0.007
Pour Point, °C	< -8
Specific Gravity (25°C)	0.985
Flash Point ^(c) °C	116

(a) Surface Tension by Wilhelmy Plate Method

- (b) Critical Micelle Concentration
- (c) Pensky-Martens Closed Cup, ASTM Method D93

4. Potential Application

QS-326 spray adjuvant has been used successfully in spray applications globally. Typical applications include:

Application	Typical Use Rate ^(a)
Plant Growth Regulators	0.025% to 0.05%
Herbicide	0.025% to 0.15%
Insecticide	0.025% to 0.1%
Fungicide	0.015% to 0.05%
Fertilizers and Micronutrients	0.015% to 0.1%

(a) Note: use rates are dependent on crop, agrochemical and spray volume requirements.



5. How To Use

In Agrochemical Formulations

QS-326 spray adjuvant may be used as a component in agrochemical formulations. Although organosilicone surfactants are subject to hydrolysis under acidic or basic conditions, optimum performance is achieved by buffering the formulation to pH 6.5 - 7.5. Additionally, it is recommended that QS-326 spray adjuvant be used at a concentration of 0.5-8%, based on the total formulation.

As A Tank Mix Adjuvant

QS-326 spray adjuvant, when used as a tank-side adjuvant may be used to improve spray coverage, improve uptake or to allow for a reduction in spray volume. QS-326 spray adjuvant is most effective as a tank-side adjuvant when spray mixtures are 1) within a pH range of 5-8, and 2) used within 24 hours of preparation.

High spray volumes, coupled with high surfactant rates, are not required to achieve sufficient coverage with QS-326 spray adjuvant. In fact, QS-326 spray adjuvant has the potential to provide adequate coverage in many low volume spray applications at rates between 0.025% and 0.1%.

6. Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

7. Product Safety, Handling and Storage

Customers should review the latest Material Safety Data Sheet (MSDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, and any special storage conditions required for safety.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Keep out of reach of children. Attention: Not for injection into humans.



OTHER PRECAUTIONS

Consult the manufacturer before using an aerosol of the neat liquid.

STORAGE

Keep container closed. store in original container.

8. Limitations

Customers must evaluate TianSheng New Materials products and make their own determination as to fitness of use in their particular applications.

9. CONTACT INFORMATION

For product prices, availability, or order placement, contact our customer service by visiting <u>http://www.jxtsxcl.com/contactus.htm.</u> For literature and technical assistance, visit our website at: <u>www.jxtsxcl.com</u>.

10. Other information

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.